## NSN 5930-01-098-7296

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-7296			
Body Style:			
Bushing mounted			
Hazardous Locations/environmental Protection:			
Corrosion resistant			
Overall Length:			
1.156 inches			
Overall Height:			
1.613 inches			
Overall Width:			
0.375 inches			
Bushing Length:			
0.375 inches			
Body Length:			
0.781 inches			
Body Width:			
0.375 inches			
Body Height:			
0.957 inches			
Case Material:			
Metal			
Actuator Diameter:			
0.156 inches			
Actuator Height:			
0.281 inches			
Actuator Color:			
Natural single actuator			
Maximum Voltage Rating In Volts:			
115.0 ac and 28.0 dc			
End Application:			
Af sat com 13499			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Threaded bushing			
Thready Qty Per Inch (tpi):			
40			
Thread Size:			
0.250 inches			
Nonpile-up Contact Arrangement:			
2 two circuit, double make, two positions momentary single switch unit			
Contact Load Current Rating At Maximum Rated Voltage:			
10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000			

amperes inductive ac and 3.000 amperes lamp ac

## NSN 5930-01-098-7296

Push Switch - Page 2 of 2



Thread	Series	Designator
Uns		

**Terminal Type And Quantity:** 

8 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0