

View Online at <https://aerobasegroup.com/nsn/5930-01-098-7894>

Body Style:

Hole mounted

Overall Length:

0.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.150 inches

Overall Height:

0.390 inches

Overall Width:

0.160 inches

Body Length:

0.300 inches

Body Width:

0.100 inches

Body Height:

0.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.065 inches

Actuator Style:

Round

Actuator Diameter:

0.100 inches

Actuator Height:

0.080 inches

Actuator Free Position Height:

0.270 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.75 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.015 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes resistive ac

Special Features:

Black cap

Precious Material And Location:

Contact surfaces gold and contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0