NSN 5930-01-098-7894

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-098-7894

Hole mounted
Overall Length:
0.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.150 inches
Overall Height:
0.390 inches
Overall Width:
0.160 inches
Body Length:
0.300 inches
Body Width:
0.100 inches
Body Height:
0.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.065 inches
Actuator Style:
Round
Actuator Diameter:
0.100 inches
Actuator Height:
0.080 inches
Actuator Free Position Height:
0.270 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:

0.75 ounces

4.0 ounces

Actuator Movement:

Switch Actuating Force:

Between 0.015 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

NSN 5930-01-098-7894

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes resistive ac

Special Features:

Black cap

Precious Material And Location:

Contact surfaces gold and contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0