NSN 5930-01-098-9273

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-098-9273

Hazardous Locations/environmental Protection:
Explosion proof
Overall Height:
3.300 inches
Overall Width:
4.750 inches
Body Height:
8.500 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Distance Between Mounting Facility Centers:
4.250 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
300.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Features Provided:
Calibrated scale and electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage and 15.0 amperes inductive load single voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+95.00/+215.00 actuation point degrees fahrenheit
Contact Adjustment Type:
Internal actuation point screw with scale
Contact Voltage Rating In Volts:
250.0 ac at sea level single voltage
Frequency In Hertz:
50.0 single voltage and 60.0 single voltage

N/a

Shelf Life:

NSN 5930-01-098-9273

Thermostatic Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0