NSN 5930-01-099-1032

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-099-1032

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Moisture resistant |
| Overall Length: |
| 0.300 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.150 inches |
| Overall Height: |
| 0.363 inches |
| Overall Width: |
| 0.100 inches |
| Body Length: |
| 0.300 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.250 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.059 inches |
| Actuator Style: |
| Leaf |
| Actuator Free Position Height: |
| 0.243 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 5.0 grams |
| Switch Actuating Force: |
| 36.0 grams |
| Actuator Movement: |

Contact Load Current Rating At Maximum Rated Voltage:

 $1.000 \ \text{amperes}$ resistive dc and $1.000 \ \text{amperes}$ inductive dc and $1.000 \ \text{amperes}$ resistive ac

Between 0.090 pretravel inches and 0.014 overtravel inches and 0.021 differential inches

NSN 5930-01-099-1032 Sensitive Switch - Page 2 of 2



| Precious Material And Location: | |
|---------------------------------|--|
| Contacts silver | |
| Terminal Type And Quantity: | |
| 3 turret | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

Fiig: A053a0