

View Online at <https://aerobasegroup.com/nsn/5930-01-099-9568>

**Thread Class:**

2b single pressure connection

**Overall Length:**

2.954 inches

**Overall Height:**

3.344 inches

**Body Height:**

2.641 inches

**Unthreaded Mounting Hole Diameter:**

0.161 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.375 inches

**Longest Vertical Distance Between Mounting Centers:**

0.750 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Capillary tube end seal connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

7.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+100.00/+450.00 actuation point pounds per square inch gage and +100.00/+450.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

400.00 actuation point pounds per square inch gage and 330.00 deactuation point pounds per square inch gage and 70.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

277.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0