

View Online at <https://aerobasegroup.com/nsn/5930-01-100-0383>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

6.499 inches

Overall Height:

6.750 inches

Overall Width:

6.750 inches

First Flat Length:

1.375 inches single actuator

Shaft Diameter:

0.625 inches single actuator

Shaft Length:

1.687 inches single actuator

Unthreaded Mounting Hole Diameter:

0.531 inches single mounting facility

Individual Section Quantity:

1

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

5.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.625 inches single mounting facility

End Application:

An/msc-64 37695

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

2 single section periphery

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+72.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0