

View Online at <https://aerobasegroup.com/nsn/5930-01-100-0383>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

6.499 inches

**Overall Height:**

6.750 inches

**Overall Width:**

6.750 inches

**First Flat Length:**

1.375 inches single actuator

**Shaft Diameter:**

0.625 inches single actuator

**Shaft Length:**

1.687 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.531 inches single mounting facility

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.625 inches single mounting facility

**End Application:**

An/msc-64 37695

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section periphery

**Throw Quantity:**

2 single section periphery

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section periphery

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Detent Rotational Torque Range:**

+0.500/+72.000 inch-pounds single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

200.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0