# NSN 5930-01-100-0708

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-100-0708



# **Thread Class:** 2a

Body Style:

Bushing mounted

## Hazardous Locations/environmental Protection:

Weatherproof

#### **Overall Length:**

1.005 inches

#### **Overall Height:**

0.375 inches

#### **Overall Width:**

0.375 inches

#### **Bushing Length:**

0.250 inches

#### Body Length:

0.375 inches

# Case Material:

euce mater

Plastic

## Actuator Diameter:

0.160 inches

### Actuator Height:

0.150 inches

# Actuator Color:

Red single actuator

#### Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

#### **End Application:**

An/arn-118 (v) 13499

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thready Qty Per Inch (tpi):

32

# Thread Size:

0.250 inches

# Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 2.000 amperes resistive ac

# **Special Features:**

Epoxy sealed terminals; silicone rubber o-ring around plunger

# NSN 5930-01-100-0708

Push Switch - Page 2 of 2



**Precious Material And Location:** 

Contacts silver

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0