

View Online at <https://aerobasegroup.com/nsn/5930-01-100-4106>

**Thread Class:**

2b all threaded hole

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.090 inches

**Overall Width:**

1.120 inches

**Distance Between Mounting Facility Centers:**

0.688 inches

**End Application:**

4120-00-168-1775 air conditioner

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

750.00 pounds per square inch gage

**Thread Size:**

0.138 inches all threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Sensing Element Burst Pressure:**

3000.00 pounds per square inch gage

**Terminal Type:**

Screw

**Contact Load Current Rating:**

1.5 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+384.00/+416.00 actuation point pounds per square inch gage and +334.00/+366.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

24.0 dc at sea level single voltage

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0