

View Online at <https://aerobasegroup.com/nsn/5930-01-100-4106>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.090 inches

Overall Width:

1.120 inches

Distance Between Mounting Facility Centers:

0.688 inches

End Application:

4120-00-168-1775 air conditioner

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

750.00 pounds per square inch gage

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

3000.00 pounds per square inch gage

Terminal Type:

Screw

Contact Load Current Rating:

1.5 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+384.00/+416.00 actuation point pounds per square inch gage and +334.00/+366.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0