## NSN 5930-01-100-4889

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

**Body Style:**Panel mounted

Overall Length: 3.766 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-100-4889

0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and green single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
Hars single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.560 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens and holding solenoid
Nonpile-up Contact Arrangement:
4 two circuit, double break/double make, both positions maintained single switch unit

## NSN 5930-01-100-4889

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:** 

Bottom half of actuator marked with a triangle

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0