# NSN 5930-01-100-4891

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-100-4891

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.706 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

## Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.100 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator and green single actuator

#### **Illuminated Actuator Color:**

White single actuator and green single actuator

## Actuator Inscription:

Man single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

3.560 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### Features Provided:

Horizontal split lens

#### Nonpile-up Contact Arrangement:

4 two circuit, double break/double make, both positions maintained single switch unit



# NSN 5930-01-100-4891

Push Switch - Page 2 of 2



### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac

#### **Special Features:**

Bottom half of actuator marked with a triangle

## Precious Material And Location:

Contacts silver

## Terminal Type And Quantity:

1 socket, integrated wire termination

#### Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A053a0