NSN 5930-01-100-4892

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.706 inches Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-100-4892

0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and green single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
Nav crs single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.560 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid and full display lens
Nonpile-up Contact Arrangement:
4 two circuit, double break/double make, both positions maintained single switch unit

NSN 5930-01-100-4892

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Bottom half of actuator marked with a triangle

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0