

View Online at <https://aerobasegroup.com/nsn/5930-01-100-4894>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

0.750 inches

**Overall Height:**

3.706 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.750 inches

**Body Height:**

3.560 inches

**Case Material:**

Metal

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.100 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator and green single actuator

**Illuminated Actuator Color:**

White single actuator and green single actuator

**Actuator Inscription:**

Loc single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Holding solenoid

**Nonpile-up Contact Arrangement:**

4 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:**

Bottom half of actuator marked with a triangle

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

21 socket, integrated wire termination

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0