NSN 5930-01-100-7064

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-100-7064

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.416 inches

Overall Height:

0.812 inches

Overall Width:

0.812 inches

Body Width:

0.679 inches

Body Height:

0.679 inches

Case Material:

Metal

Actuator Length:

0.812 inches

Actuator Style:

Rectangular

Actuator Height:

0.430 inches

Actuator Width:

0.812 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

4920-00-216-9141

Mounting Surface To Terminal End Distance:

2.950 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-100-7064

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Four terminals for lamps

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 pin and 4 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0