NSN 5930-01-100-7065

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-100-7065

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.416 inches
Overall Height:
0.812 inches
Overall Width:
0.812 inches
Body Width:
0.679 inches
Body Height:
0.679 inches
Case Material:
Metal
Actuator Length:
0.812 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.812 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
4920-00-216-9141
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit

NSN 5930-01-100-7065

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

inductive ac and 1.000 amperes lamp a
Special Features:
Four terminals for lamps
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
6 pin and 4 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0