

View Online at <https://aerobasegroup.com/nsn/5930-01-100-7891>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Bushing Length:

0.352 inches

Body Length:

0.652 inches

Body Width:

0.500 inches

Body Height:

0.527 inches

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 24.0 dc

Mounting Surface To Terminal End Distance:

0.623 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0