

View Online at <https://aerobasegroup.com/nsn/5930-01-100-8361>

Body Style:

Printed circuit

Overall Length:

Between 0.560 inches and 0.600 inches

Overall Height:

0.465 inches

Overall Width:

Between 0.370 inches and 0.405 inches

Body Length:

Between 0.560 inches and 0.600 inches

Body Width:

Between 0.370 inches and 0.405 inches

Body Height:

Between 0.230 inches and 0.300 inches

Case Material:

Plastic

Switch Actuator Quantity:

5

Actuator Length:

Between 0.045 inches and 0.065 inches

Actuator Style:

Rectangular

Actuator Height:

0.040 inches

Actuator Width:

Between 0.055 inches and 0.085 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

6.0 dc and 24.0 dc

Mounting Method:

Printed circuit

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained 5th switch unit

Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes resistive dc and 25.0 milliamperes resistive dc

Precious Material And Location:

Terminal and contact surfaces gold

Test Data Document:

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 printed circuit

Specification Data:

81349-mil-s-83504/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0