

View Online at <https://aerobasegroup.com/nsn/5930-01-101-0820>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.984 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.125 inches single actuator

Overall Diameter:

0.298 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

Radio set 37695

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

15.0 dc at sea level

Shaft Flat/slot Angular Location:

108.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Pin

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

20.0 milliamperes resistive load dc at sea level

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0