NSN 5930-01-101-3448

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-101-3448

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
2.016 inches
Overall Height:
9.906 inches
Overall Width:
3.813 inches
Body Height:
6.375 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
3.626 inches
Longest Vertical Distance Between Mounting Centers:
3.626 inches
End Application:
Mx peacekeeper missle
Tempurature Sensing Element Type:
Immersion well
Operating Tempurature Rating:
Between -100.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Terminal Type:
Screw
Contact Load Current Rating:
10.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+15.00/+140.00 actuation point degrees fahrenheit and +14.00/+137.00 deactuation point degrees fahrenheit

NSN 5930-01-101-3448

Thermostatic Switch - Page 2 of 2

Demilitarization:

No Fiig: A048b0



Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Voltage Rating In Volts:
480.0 ac at sea level first voltage
Special Features:
Weapon system essential
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure: