NSN 5930-01-101-4727

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-101-4727

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Moisture proof and shock proof

Overall Length:

3.525 inches

Overall Height:

1.200 inches

Overall Width:

1.200 inches

Body Length:

1.200 inches

Body Width:

0.975 inches

Body Height:

0.975 inches

Actuator Length:

0.740 inches

0.7 +0 1101103

Actuator Style:

Rectangular

Actuator Height:

0.300 inches

Actuator Width:

0.740 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Submarine communications and antenna systems; submarine antenna; ship, ohio class ssn (trident)

Mounting Surface To Terminal End Distance:

3.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 pin

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0