## NSN 5930-01-101-7634

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-101-7634

Body Style:		
Bushing mounted		
Hazardous Locations/environmental Protection:		
Corrosion resistant		
Overall Length:		
2.698 inches		
Overall Height:		
2.550 inches		
Overall Width:		
1.000 inches		
Case Material:		
Metal		
Actuator Style:		
Roller plunger		
Actuator Free Position Height:		
1.638 inches		
Actuator Roller Diameter:		
0.375 inches		
Actuator Roller Width:		
0.120 inches		
Housing Length:		
1.060 inches		
Housing Bushing Length:		
0.920 inches		
Maximum Voltage Rating In Volts:		
28.0 dc		
End Application:		
1440-01-087-9844		
Inclosure Type:		
Fully enclosed		
Mounting Method:		
Threaded bushing		
Thread Size:		
0.625 inches		
Nonpile-up Contact Arrangement:		
1 pole, double throw, one position momentary single switch unit		
Switch Release Force:		
C4.0 avenage		

64.0 ounces

**Switch Actuating Force:** 

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:** 

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.010 differential inches

## NSN 5930-01-101-7634

Sensitive Switch - Page 2 of 2



Contact Load Current R	Rating At Maximum	Rated Voltage:
------------------------	-------------------	----------------

5.000 amperes resistive dc

**Thread Series Designator:** 

Unef

**Terminal Type And Quantity:** 

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A053a0