## NSN 5930-01-101-7634

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-101-7634

Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.698 inches
Overall Height:
2.550 inches
Overall Width:
1.000 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.638 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.120 inches
Housing Length:
1.060 inches
Housing Bushing Length:
0.920 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
1440-01-087-9844
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
C4.0 avenage

64.0 ounces

**Switch Actuating Force:** 

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:** 

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.010 differential inches

## NSN 5930-01-101-7634

Sensitive Switch - Page 2 of 2



Contact Load Current Rating	At Maximum	Rated Voltage:
-----------------------------	------------	----------------

5.000 amperes resistive dc

**Thread Series Designator:** 

Unef

**Terminal Type And Quantity:** 

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A053a0