

View Online at <https://aerobasegroup.com/nsn/5930-01-101-7653>

**Thread Class:**

2b 2nd mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.407 inches

**Overall Height:**

2.562 inches

**Overall Width:**

2.562 inches

**Individual Section Quantity:**

2

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

2.312 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.312 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing 1st mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

32 1st mounting facility

**Thread Size:**

0.469 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Rotor Through Connection Quantity:**

1 each section

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks, breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Uns 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0