

<b>NSN 5930-01-101-7653</b> Rotary Switch - Page 1 of 2	A
View Online at https://aerobasegroup.com/nsn/5930-01-101-7653	
Thread Class:	
2b 2nd mounting facility	
Hazardous Locations/environmental Protection:	
Explosion proof	
Overall Length:	
3.407 inches	
Overall Height:	
2.562 inches	
Overall Width:	
2.562 inches	
Individual Section Quantity:	
2	
Knob Manufacturer Code:	
82121	
Longest Horizontal Distance Between Mounting Centers:	
2.312 inches 1st mounting facility	
Longest Vertical Distance Between Mounting Centers:	
2.312 inches 2nd mounting facility	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 each section front	
Throw Quantity:	
3 each section rear	
Mounting Method:	
Threaded bushing 1st mounting facility	

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.469 inches 1st mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Switch Actuator Momentary Position:** 

Clockwise single actuator

**Rotor Through Connection Quantity:** 

1 each section

**Mounting Facility Pattern:** 

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

## **NSN 5930-01-101-7653**Rotary Switch - Page 2 of 2



Terminal Type:			
Tab w/screw			
Contact Switching Action:			
Makes before breaks, breaks before makes each section rear			
Switch Actuator Positioning Increment:			
45.0 degrees single actuator			
Switch Actuator Stop Device Type:			
Fixed stop single actuator			
Contact Load Current Rating:			
10.0 amperes resistive load ac at sea level			
Style Designator:			
Tap, circuit selector			
Thread Series Designator:			
Uns 1st mounting facility			
Shelf Life:			
N/a			
Unit Of Measure:			
<del></del>			
Demilitarization:			
No			
Fiig:			
A052b0			