NSN 5930-01-101-7842

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-101-7842

Overall Height:
5.750 inches
Overall Width:
2.370 inches
Body Height:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.201 inches
Longest Horizontal Distance Between Mounting Centers:
2.720 inches
Longest Vertical Distance Between Mounting Centers:
2.720 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port and tamper proof cap
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
12000.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
50.0 milliamperes resistive load fourth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+425.00/+5640.00 actuation point pounds per square inch and +545.00/+6000.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

NSN 5930-01-101-7842Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular w/bracket
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0