

View Online at <https://aerobasegroup.com/nsn/5930-01-101-7842>

Overall Height:

5.750 inches

Overall Width:

2.370 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Longest Horizontal Distance Between Mounting Centers:

2.720 inches

Longest Vertical Distance Between Mounting Centers:

2.720 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

12000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

50.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+425.00/+5640.00 actuation point pounds per square inch and +545.00/+6000.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0