

View Online at <https://aerobasegroup.com/nsn/5930-01-102-1535>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.500 inches

**Flat Height:**

0.103 inches single actuator and 0.105 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Overall Diameter:**

0.750 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 6: 00 o'clock

**End Application:**

Multi-hull 03950

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section periphery

**Throw Quantity:**

5 single section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section periphery

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 125.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0