NSN 5930-01-102-1537

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-102-1537

Panel mount
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
3.660 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.688 inches
Body Height:
3.560 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Maximum Voltage Rating In Volts:
28.0 ac and 28.0 dc
End Application:
1560k0153096n 33875
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

NSN 5930-01-102-1537

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Two terminals for lamps; one terminal for holding coil

Terminal Type And Quantity:

12 socket, integrated wire termination and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0