NSN 5930-01-102-4079

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-102-4079

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

Between 2.425 inches and 2.950 inches

Body Length:

Between 1.875 inches and 2.400 inches

Overall Diameter:

1.150 inches

End Application:

5840-01-046-7622 radar group, tra

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.684 inches and 1.000 inches

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Outlet connection

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

120.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

800.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage and 1.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

20.50 actuation point pounds per square inch and 23.50 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

NSN 5930-01-102-4079

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Test Data Document:
81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf single pressure connection
Specification Data:
81349-mil-s-9395/27 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0