## NSN 5930-01-102-6526

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-102-6526

**Thread Class:** 

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

**Overall Length:** 

2.438 inches

**Overall Height:** 

1.531 inches

**Overall Width:** 

1.281 inches

First Flat Length:

0.625 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.750 inches single actuator

**Individual Section Quantity:** 

2

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

**End Application:** 

C-10832/arc-1 37695

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

**Throw Quantity:** 

5 2nd section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

90.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:** 

20 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-01-102-6526**Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
18.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0