NSN 5930-01-102-7432

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-102-7432

| Body Style: |
|---|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 1.561 inches |
| Overall Width: |
| 0.270 inches |
| Bushing Length: |
| 0.336 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.270 inches |
| Body Height: |
| 0.350 inches |
| Case Material: |
| Plastic |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.450 inches |
| Actuator Width: |
| 0.100 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained |
| Actuator Color: |
| Natural single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 28.0 dc |
| End Application: |
| C-10832/arc-1 37695 |
| Mounting Surface To Terminal End Distance: |
| 0.775 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |

40

NSN 5930-01-102-7432 Toggle Switch - Page 2 of 2



| Thread Size: |
|--|
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.000 amperes resistive ac |
| Special Features: |
| Epoxy sealed terminals |
| Precious Material And Location: |
| Contacts and terminal surfaces silver |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 3 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |