

View Online at <https://aerobasegroup.com/nsn/5930-01-103-4812>

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

5.450 inches

Outside Diameter:

1.000 inches single connection

Body Diameter:

2.040 inches

Body Length:

2.750 inches

Overall Diameter:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.225 inches

End Application:

Harpoon test 76301

Pressure Switch Type:

Gage

Mounting Facility Circle Radius:

2.910 inches

Operating Temperature Rating:

Between 28.0 degrees fahrenheit and 110.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position circular

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

30.00 actuation point pounds per square inch absolute and 17.00 deactuation point pounds per square inch absolute and 13.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Grooved, unthreaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0