## NSN 5930-01-103-4815

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-103-4815

Hazardous Locations/environmental Protection:
Dustproof
Overall Height:
0.369 inches
Body Diameter:
0.630 inches
Body Height:
0.349 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
End Application:
Modkitaf37ut1 36378
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
350.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
10.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
248.00 actuation point degrees fahrenheit and 212.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
277.0 ac at sea level first voltage
Media For Which Designed:
Gas
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-103-4815

Thermostatic Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0