

View Online at <https://aerobasegroup.com/nsn/5930-01-103-8005>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

5.938 inches

**Overall Height:**

8.563 inches

**Overall Width:**

2.094 inches

**Body Height:**

2.938 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.194 inches and 0.197 inches

**Distance Between Mounting Facility Centers:**

5.250 inches

**Temperature Sensing Element Type:**

Bulb

**Operating Temperature Rating:**

Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

9.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+70.00/+140.00 actuation point degrees fahrenheit and +67.00/+137.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0