

View Online at <https://aerobasegroup.com/nsn/5930-01-103-8005>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.938 inches

Overall Height:

8.563 inches

Overall Width:

2.094 inches

Body Height:

2.938 inches

Unthreaded Mounting Hole Diameter:

Between 0.194 inches and 0.197 inches

Distance Between Mounting Facility Centers:

5.250 inches

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+70.00/+140.00 actuation point degrees fahrenheit and +67.00/+137.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0