

View Online at <https://aerobasegroup.com/nsn/5930-01-103-8006>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

4.938 inches

Overall Height:

8.500 inches

Overall Width:

2.875 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

End Application:

Switch, thermo 19278

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

167.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+70.00/+140.00 actuation point degrees fahrenheit and +70.00/+140.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft with scale and external actuation point shaft with scale

Contact Voltage Rating In Volts:

440.0 dc at sea level third voltage

Special Features:

Cross ambient-monel conn; o ring; 304 ss; bulb-6800 ohm resistor

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0