

View Online at <https://aerobasegroup.com/nsn/5930-01-104-2202>

Thread Class:

2b single pressure connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.350 inches

Unthreaded Mounting Hole Diameter:

0.344 inches

Distance Between Mounting Facility Centers:

1.844 inches

End Application:

3930-01-082-3758 truck, fork lift

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

32 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.164 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

100.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+31.00/+37.00 actuation point gram and +31.00/+37.00 deactuation point gram

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unc single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0