

View Online at <https://aerobasegroup.com/nsn/5930-01-104-2202>

**Thread Class:**

2b single pressure connection

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

5.350 inches

**Unthreaded Mounting Hole Diameter:**

0.344 inches

**Distance Between Mounting Facility Centers:**

1.844 inches

**End Application:**

3930-01-082-3758 truck, fork lift

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Thready Qty Per Inch (tpi):**

32 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.164 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

100.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+31.00/+37.00 actuation point gram and +31.00/+37.00 deactuation point gram

**Contact Adjustment Type:**

External deactuation point shaft and external actuation point shaft

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unc single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0