# NSN 5930-01-104-3809

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-104-3809

## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.050 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### **Case Material:**

Metal

# Actuator Length:

Longin

0.620 inches

# Actuator Style:

Rectangular

## Actuator Height:

0.100 inches

## Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator and green single actuator

#### **Illuminated Actuator Color:**

White single actuator and green single actuator

# Actuator Inscription:

Tcn single actuator

#### Illuminated Actuator Color Sequence:

Upper half of actuator white lower half of actuator green

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.950 inches

#### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Horizontal split lens

# NSN 5930-01-104-3809

Push Switch - Page 2 of 2



# Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac

### **Special Features:**

Lower half of actuator has a triangle design

# **Precious Material And Location:**

Contacts silver

### **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A053a0