## NSN 5930-01-104-7150

Push Switch - Page 1 of 2

12 turret and 8 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5930-01-104-7150

Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Shock resistant and vibration resistant					
Overall Length:					
1.200 inches					
Overall Width:					
0.960 inches					
Body Length:					
1.183 inches					
Body Width:					
0.780 inches					
Body Height:					
2.790 inches					
Actuator Length:					
1.110 inches					
Actuator Style:					
Rectangular					
Actuator Width:					
0.870 inches					
Actuator Color:					
Green single actuator					
Illuminated Actuator Color:					
Green single actuator					
Actuator Inscription:					
Gnd off/mono-gnd single actuator					
Maximum Voltage Rating In Volts:					
125.0 ac and 28.0 dc					
End Application:					
0e-207/br 28528					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Nonpile-up Contact Arrangement:					
4 pole, double throw, one position momentary single switch unit					
Contact Load Current Rating At Maximum Rated Voltage:					
4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac					
Precious Material And Location:					
Contact surfaces silver					
Terminal Type And Quantity:					

## NSN 5930-01-104-7150

Push Switch - Page 2 of 2



-			 
٠.	hΔ	Iŧ.	ife:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0