# NSN 5930-01-104-7439

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-104-7439

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.255 inches

#### **Overall Height:**

2.312 inches

#### **Overall Width:**

1.750 inches

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

2.031 inches single actuator

#### **Nonturn Device Radius:**

# 0.531 inches at 3: 00 o'clock

## Individual Section Quantity:

1

# Nonturn Device Type:

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section rear

## **Throw Quantity:**

23 single section rear

## Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

24 single actuator

## Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Makes before breaks single section rear

# NSN 5930-01-104-7439

Rotary Switch - Page 2 of 2



**Switch Actuator Positioning Increment:** 15.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contacts and rotor surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0