

View Online at <https://aerobasegroup.com/nsn/5930-01-104-7448>

**Body Style:**

Bushing mount

**Overall Length:**

0.656 inches

**Overall Height:**

2.332 inches

**Overall Width:**

0.656 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

0.556 inches

**Body Width:**

0.556 inches

**Case Material:**

Plastic

**Actuator Length:**

0.437 inches

**Actuator Style:**

Pivoted

**Actuator Height:**

Between 1.010 inches and 1.148 inches

**Actuator Width:**

0.437 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked in and center position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

0.706 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

**Precious Material And Location:**

Contacts and terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0