

View Online at <https://aerobasegroup.com/nsn/5930-01-104-7448>

Body Style:

Bushing mount

Overall Length:

0.656 inches

Overall Height:

2.332 inches

Overall Width:

0.656 inches

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.556 inches

Body Width:

0.556 inches

Case Material:

Plastic

Actuator Length:

0.437 inches

Actuator Style:

Pivoted

Actuator Height:

Between 1.010 inches and 1.148 inches

Actuator Width:

0.437 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Precious Material And Location:

Contacts and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0