

View Online at <https://aerobasegroup.com/nsn/5930-01-104-8506>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

5.312 inches

**First Flat Length:**

0.467 inches single actuator

**Flat Height:**

0.205 inches single actuator and 0.215 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

0.470 inches single actuator and 0.530 inches single actuator

**Overall Diameter:**

1.400 inches

**Nonturn Device Radius:**

0.437 inches at 3:00 o'clock

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

212.5 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Connector, receptacle and threaded stud

**Contact Switching Action:**

Makes before breaks 1st section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0