

View Online at <https://aerobasegroup.com/nsn/5930-01-104-8514>

Body Style:

Hole mounted

Overall Length:

Between 0.490 inches and 0.510 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.178 inches and 0.198 inches

Overall Height:

Between 0.614 inches and 0.696 inches

Overall Width:

Between 0.190 inches and 0.210 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.190 inches and 0.210 inches

Body Height:

Between 0.493 inches and 0.533 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.100 inches

Actuator Height:

Between 0.031 inches and 0.073 inches

Actuator Free Position Height:

Between 0.444 inches and 0.506 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.040 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0