

View Online at <https://aerobasegroup.com/nsn/5930-01-104-8514>

**Body Style:**

Hole mounted

**Overall Length:**

Between 0.490 inches and 0.510 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.178 inches and 0.198 inches

**Overall Height:**

Between 0.614 inches and 0.696 inches

**Overall Width:**

Between 0.190 inches and 0.210 inches

**Body Length:**

Between 0.490 inches and 0.510 inches

**Body Width:**

Between 0.190 inches and 0.210 inches

**Body Height:**

Between 0.493 inches and 0.533 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.100 inches

**Actuator Height:**

Between 0.031 inches and 0.073 inches

**Actuator Free Position Height:**

Between 0.444 inches and 0.506 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.030 pretravel inches and 0.040 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0