NSN 5930-01-105-3531

Sensitive Switch - Page 1 of 2

Body Style:

Bushing mounted **Overall Length:**



View Online at https://aerobasegroup.com/nsn/5930-01-105-3531

3.310 inches
Overall Height:
1.060 inches
Overall Width:
2.310 inches
Actuator Style:
Round
Actuator Diameter:
Between 0.245 inches and 0.255 inches
Actuator Height:
0.701 inches
Housing Diameter:
Between 0.980 inches and 1.020 inches
Housing Length:
1.060 inches
Housing Bushing Length:
1.549 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:
Between 45.0 ounces and 95.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc
Thread Series Designator:
Unef
Terminal Type And Quantity:
1 connector, receptacle

NSN 5930-01-105-3531

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0