

View Online at <https://aerobasegroup.com/nsn/5930-01-105-4540>

**Thread Length:**

0.470 inches single mounting facility

**Overall Length:**

4.120 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.214 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.500 inches single actuator

**Overall Diameter:**

2.000 inches

**Nonturn Device Radius:**

0.372 inches at 6:00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Tab at 6:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

200.0 ac at sea level

**Switch Actuator Momentary Position:**

Counterclockwise single actuator

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes motor load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0